

Most Japanese manufacturers have standardised their gearbox outputs to accept a M22 x 1.5mm threaded sensor which has a round peg drive with a 'lug' pinched onto the side. Connect the Brantz meter to the sensor before fitting the sensor to the vehicle to test. Put the Brantz on to Calibration figure 001, Switch on the Brantz and rotate the inner rotor of the sensor. See the Brantz tripmeter increment. Do not proceed to fitting the sensor to the vehicle if this stage does not function correctly. Unscrew the original speedometer cable from the gearbox, gently screw in the Brantz Japanese sensor with the drive pin in place, checking that a spacer is not needed to prevent the inner rotor from binding, and screw the original speedometer cable into the sensor with the same check for binding. Technical specification: 4 pulses per revolution (20mA sink capability). Hysteresis type sensor. 5volts to 13 volts power supply.



Connect as follows:

SENSOR (BR3)	Connect To	TRIPMETER (Grey Cable)
BLACK	>	GREEN
RED	>	BROWN
WHITE	>	BLUE

Contact us: Brantz, 34 Union Road, Macclesfield, SK11 7BN, UK. Tel/Fax: 0044 (0) 1625 669366

Website: www.brantz.co.uk Email: sales@brantz.co.uk



Most Japanese manufacturers have standardised their gearbox outputs to accept a M22 x 1.5mm threaded sensor which has a round peg drive with a 'lug' pinched onto the side. Connect the Brantz meter to the sensor before fitting the sensor to the vehicle to test. Put the Brantz on to Calibration figure 001, Switch on the Brantz and rotate the inner rotor of the sensor. See the Brantz tripmeter increment. Do not proceed to fitting the sensor to the vehicle if this stage does not function correctly. Unscrew the original speedometer cable from the gearbox, gently screw in the Brantz Japanese sensor with the drive pin in place, checking that a spacer is not needed to prevent the inner rotor from binding, and screw the original speedometer cable into the sensor with the same check for binding. Technical specification: 4 pulses per revolution (20mA sink capability). Hysteresis type sensor. 5volts to 13 volts power supply.



Connect as follows:

SENSOR (BR3)	Connect To	TRIPMETER (Grey Cable)
BLACK	>	GREEN
RED	>	BROWN
WHITE	>	BLUE

Contact us: Brantz, 34 Union Road, Macclesfield, SK11 7BN, UK. Tel/Fax: 0044 (0) 1625 669366

Website: www.brantz.co.uk Email: Sales@brantz.co.uk

